

# ID1

## Switchable 3-Way/4-Way Tower Speaker w/ Dual 10" Subwoofers



### Specifications: ID1

### Mounting hardware included

Nominal Impedance	8 $\Omega$ - 4 $\Omega$
Input Sensitivity	89 dB - 89 dB
Frequency Response ( $\pm$ 0.25 dB)	60 Hz - 22 kHz - 25 - 150 Hz
Max. Continuous Power RMS	150 W - 800 W
Max. Power SPL @ 1 M	89 dB - 86 dB
Crossover Frequency	80 (switchable), 700 Hz, 3.8 kHz - 80 Hz (switchable)
Crossover Type	S4X <sup>®</sup> 4th Order
Enclosure - description	Black Gloss and Black Satin, Ported - Vented
Tweeter - part	1.12" Titanium Inverted Dome
Midrange - part	3" Soft Dome
Woofers - part	6.5" Kevlar Cone With Rubber Surround & Cast Frame
Subwoofer - part	10" Mica-Graphite Poly Cone with Cast Frames and Rubber Surrounds
Inputs	Gold-Plated; #2 AWG Max
Binding Posts	Gold-plated; #2 AWG wire
Height (SM = Height)	1422.4 mm / 56 in
Diameter (SM = Width)	279.4 mm / 11 in
Weight	38.55 kg / 85 lb
Accessories Optional	A2 Subwoofer Amplifier

## Description

The popular, floor standing ID1 incorporates dual 10" subwoofers plus a 3-way speaker design for compact space requirements. Switchable passive subwoofer crossover converts the ID1 to a 4-way speaker. Included accessories: chrome finished adjustable carpet spikes.

## Patented Induction Dynamics Technologies

Induction Dynamics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Induction Dynamics innovations are protected by multiple U.S. and international patents, which explicitly cover Induction Dynamics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Induction Dynamics resellers and end users.

## Technical Data and Specification

## Tools

### Technical Data

Induction Dynamics strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at [www.soundtube.com](http://www.soundtube.com). Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

### Data Acquisition and Verification

All data for Induction Dynamics speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are

compiled into a variety of formats including EASE 4.x, GLL and CLF.

## Architectural Specifications

No specifications currently.

### Induction Dynamics

8005 W. 110th St. | Suite 208  
Overland Park, KS 66210  
Phone 913.663.5600  
Fax  
Toll Free 855.663.5600  
<http://inductiondynamics.mseaudio.com>  
All Induction Dynamics products come with a 5-year limited warranty.

---

# ID1 Switchable 3-Way/4-Way Tower Speaker w/ Dual 10" Subwoofers

---



## **Optional Accessories**

**A2 Subwoofer Amplifier**