

ID1.15

4-Way Tower Speaker w/ Dual 15" Subwoofers



Specifications: ID1.15

Mounting hardware included

Nominal Impedance	8 Ω - 4 Ω
Input Sensitivity	90 dB - 90 dB
Frequency Response (\pm 0.25 dB)	60 - 22,000 Hz - 21 - 150 Hz
Max. Continuous Power RMS	150 W - 1,000 W
Max. Power SPL @ 1 M	87 dB - 87 dB
Crossover Frequency	80 (switchable); 500; 3,700 Hz - 80 Hz (switchable)
Crossover Type	S4X [®] 4th Order
Enclosure volume	Ported - Vented
Enclosure - description	Black Gloss and Black Satin
Tweeter - part	1.12" Titanium Inverted Dome
Midrange - part	3" Soft Dome
Woofers - part	8" kevlar cone with coated foam surround & cast frame
Subwoofer - part	15" Talc-filled polypropylene cones with polyether surrounds and cast frames
Inputs	Gold-Plated; #4 AWG Max
Binding Posts	Gold-plated; #2 AWG wire
Height (SM = Height)	1587.5 mm / 62.5 in
Diameter (SM = Width)	469.9 mm / 18.5 in
Weight	86.18 kg / 190 lb
Accessories Optional	A2 Subwoofer Amplifier

ID1.15

4-Way Tower Speaker w/ Dual 15" Subwoofers



Description

Massive dual 15" subwoofers and an 8" mid-woofer in a high-power, 4-way floor standing speaker minimize floor space requirements for multiple subwoofers. A switch separates the subwoofers for use in home theater applications by switching out the internal 80 Hz crossover so that the two subs can be separately powered by a subwoofer amplifier. Comes with carpet spikes.

Patented Induction Dynamics Technologies

Induction Dynamics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Induction Dynamics innovations are protected by multiple U.S. and international patents, which explicitly cover Induction Dynamics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Induction Dynamics resellers and end users.

Technical Data and Specification Tools

Technical Data

Induction Dynamics strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for Induction Dynamics speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA,

TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

Induction Dynamics

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax
Toll Free 855.663.5600
<http://inductiondynamics.mseaudio.com>
All Induction Dynamics products come with a 5-year limited warranty.

ID1.15

4-Way Tower Speaker w/ Dual 15"
Subwoofers



Optional Accessories

A2 Subwoofer Amplifier