

S2.1 & S2.r

2-Way Corner Speaker



Specifications: S2.1 & S2.r

Mounting hardware included

Nominal Impedance	4 Ω
Sensitivity dB @ 2.83V/1M	88 dB
Sensitivity dB @ 1W/1M (2)	85 dB
Frequency Response (± 3 dB)	55 Hz - 22 kHz
Max. Continuous Power RMS	175 W
Crossover Frequency	2.5 kHz
Crossover Type	2-Way S4X [®] 4th Order
Enclosure - description	Sealed
Tweeter - part	1.12" Inverted Titanium Dome
Woofer - part	6.5" Kevlar Cone With Rubber Surround & Cast Frame
Binding Posts	Gold-plated; #4 AWG Max
Height (SM = Height)	15.25"
Diameter (SM = Width)	8.5"
Weight	22 lbs

S2.l & S2.r

2-Way Corner Speaker



Description

S4X[®] circuitry compensates for on-wall 45° baffle effects. Mounts on side wall. A S2.r and S2.l can be wired in or out of phase with each other to create a side-wall dipole or bipole speaker.

Patented Induction Dynamics Technologies

Induction Dynamics and MSE Audio Group constantly develop new technologies that enhance audio product performance. Induction Dynamics innovations are protected by multiple U.S. and international patents, which explicitly cover Induction Dynamics dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect Induction Dynamics resellers and end users.

Technical Data and Specification Tools

Technical Data

Induction Dynamics strives to provide complete and

effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE[™] data - 3-D polar plots. EASE[™] Address - 2-D modeling for distributed systems Autodesk[®] Revit[®] software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC[™] - Proprietary speaker placement software

Data Acquisition and Verification

All data for Induction Dynamics speakers are independently collected from and verified by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural

Specifications

No specifications currently.

Induction Dynamics

8005 W. 110th St. | Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax
Toll Free 855.663.5600
<http://inductiondynamics.mseaudio.com>
All Induction Dynamics products come with a 5-year limited warranty.

S2.1 & S2.r

2-Way Corner Speaker

