

C SERIES

C1 • C1.iw • C1.w • C1.8 • C1.8iw • C1.8w • C2 • C2.iw • C2.w

The center channel is crucial to any surround sound system, as it's the speaker dedicated to the reproduction of front-and-center dialogue. Induction Dynamics' C Series produces crisp, clear dialogue and special effects at any volume.

S4X® Crossovers optimize frequency response - music and that changes dramatically in content won't fade in and out, but will maintain its coherence as it seamlessly crosses over from one driver to the next. Frequencies critical to human speech, like those that deliver consonants "S" and "C," sound as natural coming from the C Series as they do in real life, ensuring your high-definition video has realistic audio to match.



C SERIES

C1 • C1.iw • C1.w • C1.8 • C1.8iw • C1.8w • C2 • C2.iw • C2.w

C1



Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 6.5" Kevlar
Dimensions: 9.75" H x 28.25" W x 8" D

C1.iw



Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 6.5" Kevlar
Dimensions: 13.5" H x 29.5" W x 3.875" D
Cutout Dimensions: 12.5" H x 12.5626" W

C1.w



Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 6.5" Kevlar
Dimensions: 13.5" H x 29.5" W x 4.25" D

C1.8



Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω (2.5 minimum)
Frequency Responses: 70 Hz - 20 kHz
Power Handling: 400 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 11.75" H x 31.75" W x 10" D

C1.8iw



Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω (2.5 minimum)
Frequency Responses: 70 Hz - 20 kHz
Power Handling: 400 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 13.5" H x 45.5" W x 3.875" D
Cutout Dimensions: 12.5" H x 44.375" W

C1.8iw



Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω (2.5 minimum)
Frequency Responses: 70 Hz - 20 kHz
Power Handling: 400 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 13.5" H x 45.5" W x 4.25" D

C2



Crossover Frequencies: 2.5 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: N/A
Woofer: (2) 6.5" Kevlar
Dimensions: 8.5" H x 22.125" W x 8" D

C2.iw



Crossover Frequencies: 2.5 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: N/A
Woofer: (2) 6.5" Kevlar
Dimensions: 13.5" H x 29.5" W x 3.875" D
Cutout Dimensions: 12.5" H x 28.5625" W

C2.w



Crossover Frequencies: 2.5 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 300 W
Tweeter: 1.125" inverted titanium dome
Midrange: N/A
Woofer: (2) 6.5" Kevlar
Dimensions: 8.5" H x 27.75" W x 4.25" D