

S1 SERIES

S1 • S1.iw • S1.w • S1.8 • S1.8iw • S1.8w • S1.8Siw • S18Sw • S1.8T

With 3-way freestanding, in-wall, and on-wall options available you'll have complete freedom to customize your home entertainment system. Like all Induction Dynamics speakers, the S1 Series incorporates patented S4X® crossovers, even in the low-profile wall-mounted models.



S1 SERIES

S1 • S1.iw • S1.w • S1.8 • S1.8iw • S1.8w • S1.8Siw • S18Sw • S1.8T



S1



Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 150 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: 6.5" Kevlar
Dimensions: 22.25" H x 8.5" W x 8" D



S1.iw

Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 150 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: 6.5" Kevlar
Dimensions: 24.75" H x 13.5" W x 3.875" D
Cutout Dimensions: 23.75" H x 12.626" W



S1.w

Crossover Frequencies: 700; 3.8 kHz
Nominal Impedance: 4Ω
Frequency Responses: 55 Hz - 22 kHz
Power Handling: 150 W
Tweeter: 1.125" inverted titanium dome
Midrange: 3" soft dome
Woofer: 6.5" Kevlar
Dimensions: 24.75" H x 13.5" W x 4.25" D



S1.8

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 50 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: 8" Kevlar
Dimensions: 24.75" H x 10.5" W x 10" D



S1.8iw

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 50 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: 8" Kevlar
Dimensions: 29.5" H x 13.5" W x 3.875" D
Cutout Dimensions: 28.5626" H x 12.5" W



S1.8w

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 50 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: 8" Kevlar
Dimensions: 29.5" H x 13.5" W x 4.25" D



S1.8Siw

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 50 Hz - 20 kHz
Power Handling: 200 W
Tweeter: (2) 1.125" high-powdered soft dome
Midrange: (2) 3" soft dome
Woofer: 8" Kevlar
Dimensions: 29.5" H x 13.5" W x 6.125" D
Cutout Dimensions: 28.5626" H x 12.5" W



S1.8Sw

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 50 Hz - 20 kHz
Power Handling: 200 W
Tweeter: (2) 1.125" high-powdered soft dome
Midrange: (2) 3" soft dome
Woofer: 8" Kevlar
Dimensions: 29.5" H x 13.5" W x 6.25" D



S1.8T



Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 36 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 53.75" H x 10.5" W x 10" D



S1.8Tiw

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 36 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 54.5" H x 13.5" W x 3.875" D
Cutout Dimensions: 53.375" H x 12.5" W



S1.8Tw

Crossover Frequencies: 500; 3.7 kHz
Nominal Impedance: 4Ω
Frequency Responses: 36 Hz - 20 kHz
Power Handling: 200 W
Tweeter: 1.125" high-powdered soft dome
Midrange: 3" soft dome
Woofer: (2) 8" Kevlar
Dimensions: 54.5" H x 13.5" W x 4.25" D